



INDUSTRIAL



**Solid Carbide Spektra™ Extreme Tool Life Coated 15°, 30° & 45° Degree
Single Flute Engraving Router Bits**

CNC Operating Spindle Speed: 18,000 RPM / Depth of Cut: 1 x Tool Diameter

Material	(Tip Width) 0.005" 15°		(Tip Width) 0.005" - 0.030" 30°		(Tip Width) 0.042" 45°	
	Feed Rate IPM*	Chip Load Per Tooth IPR**	Feed Rate IPM*	Chip Load Per Tooth IPR**	Feed Rate IPM*	Chip Load Per Tooth IPR**
	Soft Wood	50" - 125"	0.003" - 0.007"	50" - 125"	0.003" - 0.007"	50" - 125"
Hard Wood	50" - 125"	0.003" - 0.007"	50" - 125"	0.003" - 0.007"	50" - 125"	0.003" - 0.007"
Soft Plastic	50" - 125"	0.003" - 0.007"	50" - 125"	0.003" - 0.007"	50" - 125"	0.003" - 0.007"
Hard Plastic	50" - 125"	0.003" - 0.007"	50" - 125"	0.003" - 0.007"	50" - 125"	0.003" - 0.007"
Solid Surface	50" - 125"	0.003" - 0.007"	50" - 125"	0.003" - 0.007"	50" - 125"	0.003" - 0.007"

Tool Reference #'s		
15°	30°	45°
45611-K	—	—
—	45620-K	—
—	—	45622-K
—	45630-K	—
—	45771-K	—
—	45771-MK	—
—	45773-K	—
—	—	45632-K
—	45774-K	—

IPM* Inches per minute
IPR** Inches per revolution

Depth of Cut: 1 x D Use recommended feed rate
2 x D Reduce feed rate by 25%
3 x D Reduce feed rate by 50%

Simple Machining Calculations:

- To find **RPM:** (SFM x 3.82) / diameter of tool
- To find **SFM:** 0.262 x diameter of tool x RPM
- To find **Feed Rate IPM:** RPM x # of flutes x chip load
- To find **Chip Load:** Feed Rate IPM / (RPM x # of flutes)
- To find **Ramp Down:** Feed Rate IPM / # of flutes

Disclaimer: It is important to understand that these values are only recommendations.

© Copyright Amana Tool® All Rights Reserved